

# **Specification Sheet**

## Model # DC32WI-88





### **Key Features:**

- 3.5" (87mm), 8/8 ohm
- Voice Range, 4 watts
- Ferrite magnet, red acrylic treated cloth cone;

## **Product Specifications & Parameters**

### **Primary Specifications**

Speakers Environment	Out	door
RoHS Compliant	No	
Technical Specifications		
		Units of Measure
Nominal Basket Diameter	3.5	inch
	87.0	mm
Rated Impedance	8	ohms
Rated Power	4.0	Watts
Program Power	8	Watts
Frequency Range	270 - 6500	Hz
Sensitivity (2.83 V input measured at 1 Meter)	90	dB SPL
Voice Coil Diameter	0.7 / 17.8	inch / mm
Magnet Weight	2.4 / 68	oz / gr
Transformer		

#### **Small Signal Parameters**

0			
		Units of Measure	
Resonant Frequency (fo)	300	Hz	
D.C. Resistance (Re)	6.3	ohms	
Mechanical Q (Qms)			
Electrical Q (Qes)			
Total Q (Qts)			
Compliance Equivalent Volume (Vas)		ltr	
BL Product (BL)		T-M	
Maximum Linear Excursion (Xmax)	1.3	mm	
Surface Area of Cone (Sd)		cm2	
Moving Mass (Mmd)		g	
Material Descriptions			
Design of Orest			

Basket	Stamped Steel
Terminal Size	0.19 x 0.02
Magnet	Ferrite
Voice Coil Wire	Copper
Voice Coil Form	Aluminum
Cone	Red Acrylic Treated Cloth
Cone Edge	Red Acrylic Treated Cloth
Dust Cap	Felt

## Drawing

ID	Description	Measurement s	Toleranc e
OD	Outside Diameter	3.5 in.	+/- 0.040"
CD	Cutout Diameter	3.1 in.	+/- 0.030"
MG	Magnet Diameter	2.1 in.	+/- 0.050"
HD	Hole Diameter	0.2 in.	+/- 0.020"
MD	Mounting Diameter	3.9 in.	+/- 0.020"
ID	Internal Depth	1.2 in.	Maximu m
FT	Flange Thickness	0.1 in.	+/- 0.050"
NW	Net Weight	227.0 gr.	

