

MODEL: BJ21-01B

5-1/4" Sub-woofer with 2.1 Channel Class D Amplifier, Black MDF Enclosure & Grille

- High Efficiency 2.1 Channel Class D Amplifier
- 5-1/4" Long-Throw Woofer with Poly Cone and Rubber Surround
- 12VAC or 12-24VDC Input
- Stereo Full Range Satellite Speaker Outputs
- 45 to 20kHz System Rated Frequency Range (With Select Full Range Drivers)
- 100 dB SPL Max Woofer Output (Satellites Dependent on Selected Models)
- 7-7/16" Cube, Ported, Black MDF Construction
- **MADE IN THE USA**

| Amplifier Output Specifications | | | | |
|---------------------------------|--------------|-------------------|-------|----------------------|
| Channel Type | Power Supply | Speaker Impedance | THD+N | Output Power (Watts) |
| Left or Right Full Range | 12VDC | 8 Ω | 1% | 8 |
| Left or Right Full Range | 18-24VDC | 8 Ω | 1% | 13.5 |
| Left or Right Full Range | 12VDC | 8 Ω | 10% | 10 |
| Left or Right Full Range | 18-24VDC | 8 Ω | 10% | 17.5 |
| Subwoofer | 12VDC | 4 Ω | 1% | 15.5 |
| Subwoofer | 18-24VDC | 4 Ω | 1% | 27 |
| Subwoofer | 12VDC | 4 Ω | 10% | 19.5 |
| Subwoofer | 18-24VDC | 4 Ω | 10% | 35 |

Amplifier Key Features

- 110Hz 18/dB Octave Crossover
- Subsonic Filter on Subwoofer Channel
- Optimized Mid-Range and High-Frequency Active Equalization
- Adjustable Volume and Woofer Level Controls
- Color Coded RCA Connectors for Full Range Speaker Hook-up
- 3.5mm Stereo "Mini-Jack" Audio Input
- 6.5mm Barrel with 2.1mm Center Pin Power Connector
- LED Power Light

