

The TK-102 system is a great choice for kiosks and digital signage where highly intelligible sound is required, as well as gaming consoles in need of more audio excitement. The enclosed speakers are ready to drop into your cabinet and the amplifier can work with your 9V - 24V power supply. Don't risk less than ideal sound via a la carte product choice, MISCO has done the work for you by pairing the right amplifier with the right speakers. While low in cost, the 102 provides plenty of high-quality sound output thanks to the perfect match of the amplifier to speakers.

Speakers

- 2.5" (64 mm) enclosed, wide range
- 4-Ohm, 6 Watt, 88 dB sensitivity
- Supplied enclosures ensure consistent audio quality
- Cloth surround for extended lifespan

Amplifier

- Power output: 12.5W x 2
- PCB style, w/ volume control
- Wide 9-24VDC rail voltage input range
- Available MISCO power supplies 36174 or PS15-VDC (sold separately)

This kit includes:

- Satellite - 90202 (x2)
- Amplifier - [93101](#)
- Wire Harness - 36173



Primary Specifications

Speaker System Type	Full Range
Enclosed Woofer Style	None
Subwoofer Type	None
Digital Signal Processing	No
Audio Signal Input	Analog

Primary Specifications

8 Ω both HF channels driven (Watts RMS)	13.5
Total Low Frequency (Sub-woofer) Output Power per channel into 4 Ω . (Watts)	9.5
Digital Input S/PDIF	No

Dimensions & Weight

PCB Size (HxWxL) (mm)	15.3 x 57.1 x 63.7
-----------------------	--------------------

Power Supply Specifications

