

The TK-201 system is a great choice for gaming consoles, kiosks, digital signage, and dozens of other applications where you need full range sound from a compact package. It's our lowest priced 2.1 channel system (with woofer). The amplifier is built-in to the woofer enclosure for easier mounting and can work with your 12V – 24V power supply. Don't risk less than ideal sound via a la carte product choice, MISCO has done the work for you by pairing the right amplifier with the right speakers.

Satellite Speakers

- 2" x 3.5" (50 x 90mm) oval shape, wide range
- 8-Ohm, 10 Watts, 84 dB sensitivity
- Neodymium magnet
- Pre-wired, ready to plug into the amplifier
- Cloth surround for long life

Subwoofer

- 3" woofer driver
- Ported low-resonance MDF (Medium Density Fiberboard) enclosure
- Mounting brackets with vibration dampening grommets for easy mounting

Amplifier (built-into woofer enclosure)

- 2.1 Channel, 55W
- Volume control
- Bass volume control
- Crossover and EQ filters factory pre-set for maximum sound quality and reliability
- 12VAC or 12-24VDC rail power supply
- Available MISCO external power supply PS15-VDC (sold separately)
- 3.5mm stereo "mini-jack" audio input

This kit includes:

- Satellite - 900N08-1LSA (x2)
- Subwoofer - [BJ21-06](#)
- Amplifier - [93105](#)



Primary Specifications

Speaker System Type	2 Way
Enclosed Woofer Style	Ported
Sub-Woofer Type	Powered [active]
Digital Signal Processing	No
Audio Signal Input	Analog

Primary Specifications

8 Ω both HF channels driven (Watts RMS)	10
Total Low Frequency (Sub-woofer) Output Power per channel into 4 Ω. (Watts)	7
Digital Input S/PDIF	No

Dimensions & Weight

PCB Size (HxWxL) (mm)	0.98" x 4.25" x 6.3" (25 mm x 108 mm x 67 mm)
------------------------------	---

Power Supply Specifications

Barrel Plug Connector Size (mm)	2
--	---

