MISCO SoundSolutions

2.1 CH. HIGH-PERFORMANCE AMPLIFIED AUDIO SYSTEM W/ SUBWOOFER

PART #: TK-401

The TK-401 system is a great choice when you want the performance certainty and consistency of self-enclosed speakers. The PC board style amplifier is ready to be integrated alongside your electronics package. A supplied wiring harness with slip-on connectors makes assembly easy, foolproof and fast. Don't risk less than ideal sound via a la carte product choice, MISCO has done the work for you by pairing the right amplifier with the right speakers.

Satellite Speakers

- 3" (76mm) Polypropylene cone wide range driver
- Neodymium magnet
- Rubber surround for long life
- Rigid glass-filled Injection molded enclosure

Sub-Woofer

- 5.25" paper cone woofer with Polyether foam surround
- 8-Ohm, 50-Watt, 87dB sensitivity
- Ported low-resonance MDF (Medium Density Fiberboard) enclosure

Amplifier

- 2.1 Channel amp, Class D, PCB style with DSP
- Cool-running, reliable Class D operation
- Up to 28W total power output
- Recommended power supply 24V DC
- Optional MISCO power supply 36162

Wiring harness with quick-connect terminations include

This kit includes:

- Satellite - 90201(x2)
- Subwoofer - SB52-A
- Amplifier - 93110
- Wire Harness - 36155

Primary Specifications

Speaker System Type	2 Way
Enclosed Woofer Style	Ported
Subwoofer Type	Powered [active]
Digital Signal Processing	Yes
Audio Signal Input	Analog

©2026 MISCO/Minneapolis Speaker Company Inc.

2.1 CH. HIGH-PERFORMANCE AMPLIFIED AUDIO SYSTEM W/ SUBWOOFER

PART #: TK-401

Primary Specifications

8 Ω both HF channels driven (Watts RMS)	20
Total Low Frequency (Sub-woofer) Output Power per channel into 4 Ω. (Watts)	8
Digital Input S/PDIF	Yes

Dimensions & Weight

PCB Size (HxWxL) (mm)	0.72" x 4.25" x 6.38" (18 mm x 108 mm x 162 mm)

Power Supply Specifications

©2026 MISCO/Minneapolis Speaker Company Inc.