MISCO
Accessories

15V, 40W POWER SUPPLY, AC-DC SINGLE OUTPUT DESKTOP
PART #: GS40A15-P1J

GS40A15-P1J is a universal AC input powers supply and is protected against short circuit / overload and over voltage. An LED light indicates when the power is on.

- Universal AC input
- 3 pole AC inlet IEC320-C14
- Fully enclosed plastic case
- Approvals include: UI / CUL / TUV / BSMI / CB / FCC /CE
- Rated current: 2.67 amps
- Output DC voltage: 15 volts
- Rated power: 40 watts
- Input AC voltage: 90 - 264 volts AC

MISCO recommends using the PC-6 cord with this power supply to ensure reliability.



Primary Specifications

- Universal AC input
- 3 pole AC inlet IEC320-C14
- Fully enclosed plastic case
- Approvals include: UI / CUL / TUV / BSMI / CB / FCC /CE
- Rated current: 2.67 amps
- Output DC voltage: 15 volts
- Rated power: 40 watts
- Input AC voltage: 90 - 264 volts AC

©2026 MISCO/Minneapolis Speaker Company Inc.

MISCO Accessories

15V, 40W POWER SUPPLY, AC-DC SINGLE OUTPUT DESKTOP

PART #: GS40A15-P1J

OUTPUT

Dc Voltage	5V
Rated Current	9A
Current Range	0 - 5A
Ripple & Noise (Max)	100mVp-p
Voltage Tolerance	+-5.0%
Line Regulation	+/-1.0%

INPUT

Voltage range	90 - 264 VAC
Frequency Range	47 - 63 Hz
Efficiency (Typical)	80.50%
AC Current	1 A / 115 V
Inrush current	65A / 230VAC

Protection

Overload	015 - 150% rated output Power
Over voltage	5.25 - 6.75 V

Environment

Working Temp	-30 - +C60
Working Humidity	20% - 90% RH
Storage Temperature	-40 - +85C, 10 - 95% RH
Temperature Coefficient	+/- 0.03%/ C
Vibration	10 - 500 Hz, 2G, 10 min/1 cycle

Safety & EMC

Stafety Standards	UL60950-1

CONNECTOR

Plug	Standard type P1J: 2.1 * 5.5*11mm, tuning fork type, center positive for stock

©2026 MISCO/Minneapolis Speaker Company Inc.