

MISCO's JC5WP-8A wide range driver is ideal for menu boards and mass transit applications in need of high-quality voice reproduction. Choose the speaker that can handle more power, thanks to a large, 1" voice coil. A waterproof treatment ensures a long-lasting solution in your next sound project.

- Wide Range Driver
- 5" (127 mm) Diameter
- 20 Watts, 8 Ohms
- 1" Voice Coil
- Acrylic Treated Cloth Cone
- 95 dB SPL



Primary Specifications

Size, Nominal (inch & mm)	5" (127 mm)
Rated Impedance (Ω)	8
Sensitivity (dB SPL) ¹	95
Frequency Range (Hz)	120 - 8,000
Resonant Frequency (Fs) (Hz)	200

More Specifications

Application	Outdoor , Transit, Voice Communications
RoHS Compliant	No
DC Resistance (Re) (Ω)	8
Program Power (W)	40

Small Signal Parameters

Nominal Impedance (Z) (Ω)	8
DC Resistance (Re) (Ω)	8
Resonant Frequency (Fs) (Hz)	200
Total Q Factor (Qts)	0.91

Material Descriptions

Basket Type	Stamped Steel
Terminal Size (mm)	5.2 mm x 0.5 mm
Voice Coil Diameter (mm)	25.81
Voice Coil Wire Material	High Temperature Copper
Voice Coil Former Material	Aluminum
Magnet Material	Ferrite
Magnet Weight (g)	283.5
Cone Body Material	Acrylic Treated Cloth
Cone Surround Material	Acrylic Treated Cloth
Spider Material	Cotton
Dust Cap Material	Acrylic Treated Cloth
Net Weight (kg)	0.76

