

The JC80WP 8" waterproof loudspeaker performs best in installations needing both excellent sound quality and durability under tough environmental conditions. This model features a treated paper cone and a piezo tweeter phase-coupled to the low frequency driver to cut phase distortion and produce an extended frequency range.

- Extended Range Coaxial with Piezo Tweeter
- 8" (203 mm) Diameter
- 15 Watts, 8 Ohms
- -67°F (-55°C) to +185°F (+85°C)
- Acrylic Treated Cloth Cone
- 93 dB SPL



Primary Specifications

Size, Nominal (inch & mm)	8" (203 mm)
Rated impedance (Ω)	8
Sensitivity (dB SPL) ¹	93
Frequency range (Hz)	50 - 18k
Resonant Frequency (Fs) (Hz)	100

More Specifications

RoHS Compliant	No
DC resistance (Re) (Ω)	8
Power, Program (W)	30

Small Signal Parameters

Nominal Impedance (Z) (Ω)	8
DC resistance (Re) (Ω)	8
Resonant Frequency (Fs) (Hz)	100
Total Q factor (Qts)	0.79

Material Descriptions

Basket type	Stamped Steel
Terminal size	5.2 x 0.5
Voice coil diameter (mm)	25.781
Voice coil wire material	High Temperature Copper
Voice coil former material	Aluminum
Magnet Material	Ferrite
Magnet weight (gm)	283.5
Cone body material	Acrylic Treated Cloth
Cone surround material	Acrylic Treated Cloth
Spider Material	Cotton
Dust cap material	Paper Composite
Net weight (kg)	2.02