

THIS IS A "BUILT TO ORDER" PRODUCT.

REQUEST A QUOTE

For a high compliance 4" driver resistant to corrosion and moisture, choose the JC5FD. This compact driver is ideal for low-level distribution systems looking for superior sound dispersion. A rugged steel frame and a treated cloth cone help support reliable sound while remaining environmentally resistant.

- Wide range speaker
- 4" (102 mm) steel basket diameter
- 15 watts, 8 ohms, 93 dB SPL
- 10 oz. ferrite magnet, treated cloth cone



Primary Specifications

Size, Nominal (inch & mm)	4" (100 mm)
Rated Impedance (Ω)	8
Sensitivity (dB SPL) ¹	93
Frequency Range (Hz)	60 - 12, 000
Resonant Frequency (Fs) (Hz) +/- 15%	85

More Specifications

Application	Indoor, Transit, Voice Communications
RoHS Compliant	No
Program Power (W)	30

Small Signal Parameters

Nominal Impedance (Z) (Ω)	8
Resonant Frequency (Fs) (Hz) +/- 15%	85
Total Q Factor (Qts)	1.50

Material Descriptions

Basket Type	Stamped steel
Magnet Material	Ferrite
Magnet Weight (g)	283.5
Cone Body Material	Treated cloth

