

THIS IS A "BUILT TO ORDER" PRODUCT.

**REQUEST A QUOTE**

For a high compliance 4" driver resistant to corrosion and moisture, choose the JC5FD. This compact driver is ideal for low-level distribution systems looking for superior sound dispersion. A rugged steel frame and a treated cloth cone help support reliable sound while remaining environmentally resistance.

- Full range speaker
- 4" (102 mm) steel basket diameter
- 15 watts, 8 ohms, 93 dB SPL
- Ferrite magnet, treated cloth cone



#### Primary Specifications

<b>Size, Nominal (inch &amp; mm)</b>	4" (102 mm)
<b>Rated Impedance (<math>\Omega</math>)</b>	8
<b>Sensitivity (dB SPL) <sup>1</sup></b>	93
<b>Frequency Range (Hz)</b>	60 - 12, 000
<b>Resonant Frequency (Fs) (Hz)</b>	85

### More Specifications

<b>Application</b>	Indoor, Transit, Voice Communications
<b>RoHS Compliant</b>	No
<b>Program Power (W)</b>	30

### Small Signal Parameters

<b>Nominal Impedance (Z) (<math>\Omega</math>)</b>	8
<b>Resonant Frequency (Fs) (Hz)</b>	85
<b>Total Q Factor (Qts)</b>	1.5

### Material Descriptions

<b>Basket Type</b>	Stamped steel
<b>Magnet Material</b>	Ferrite
<b>Magnet Weight (gm)</b>	283.5
<b>Cone Body Material</b>	Treated cloth