

The DT-15D features a 1.5" silk dome tweeter with an attached plastic diffuser to increase high frequency dispersion. An M4 tapped hole in the back of the neodymium magnet housing allows coaxial mounting to other speakers or from the rear in an enclosure. This model matches well with 5.25-8" woofers as either a coaxial addition or in a two-way system.

- Silk dome tweeter
- 1.5" (40 mm) molded resin basket diameter
- 15 watts, 8 ohm, 89 dB SPL
- High energy neodymium magnet
- M4 tapped hole for easy mounting

For this tweeter with a titanium dome, see [DT-15B](#).



Primary Specifications

Size, Nominal (inch & mm)	1" (25 mm)
Rated Impedance (Ω)	8
Sensitivity (dB SPL) ¹	89
Frequency Range (Hz)	2, 000 - 20, 000
Resonant Frequency (Fs) (Hz)	1900

More Specifications

Application	Auto / Motorcycle, High-End Audio and Home Theater, Home Audio, Indoor, Pro Sound, Voice Communications
RoHS Compliant	Yes
DC Resistance (Re) (Ω)	7.0
Program Power (W)	10

Small Signal Parameters

Nominal Impedance (Z) (Ω)	8
DC Resistance (Re) (Ω)	7.0
Resonant Frequency (Fs) (Hz)	1900
Mechanical Q Factor (Qms)	2.23
Electrical Q Factor (Qes)	4.34
Total Q Factor (Qts)	1.35

Material Descriptions

Basket Type	Molded resin
Terminal Size (mm)	2.8 x 0.5
Voice Coil Diameter (mm)	22
Voice Coil Wire Material	Copper
Magnet Material	Neodymium
Cone Body Material	Silk dome
Net Weight (kg)	0.3

