

An audio speaker/grill/lead-set assembly that delivers reliable voice communications, signals, and alarms in outdoor audio systems. This model includes a 3" wide range driver with a waterproof cone and a 2.4 Oz ferrite magnet, a square aluminum grill pre-mounted to the basket, and a 5" leadset with a protective weather shroud for extra coverage against environmental hazards like rain, wind, heat, or dust.

- Wide range speaker
- 3" (77 mm) steel basket diameter
- 4 watts, 8 ohm, 93 dB SPL
- 0.6" copper voice coil, Kapton former
- 2.4 Oz magnet, environmental-resistant cone treatment
- 4x4" aluminum grill, black powder coat
- 5" Faston connector leadset (male), 16 AWG



Primary Specifications

Size, Nominal (inch & mm)	3" (77 mm)
Rated Impedance (Ω)	8
Sensitivity (dB SPL) ¹	93
Frequency Range (Hz)	600 - 9000
Resonant Frequency (Fs) (Hz) +/- 15%	1100

More Specifications

Application	Outdoor , Signal / Alarm Systems, Transit, Voice Communications
DC Resistance (Re) (Ω)	6.3
Program Power (W)	8

Small Signal Parameters

Nominal Impedance (Z) (Ω)	7
DC Resistance (Re) (Ω)	6.3
Resonant Frequency (Fs) (Hz) +/- 15%	1100

Material Descriptions

Basket Type	Stamped steel
Terminal Size (mm)	4.8 x 0.5
Voice Coil Diameter (mm)	15.2
Voice Coil Wire Material	Copper
Voice Coil Former Material	Kapton
Magnet Material	Ferrite
Magnet Weight (g)	66.7
Cone Body Material	Acrylic treated textile
Cone Surround Material	Acrylic treated textile
Dust Cap Material	Acrylic treated textile
Net Weight (kg)	0.29

