



### Primary Specifications

<b>Size, Nominal (inch &amp; mm)</b>	2" (50 mm)
<b>Rated Impedance (<math>\Omega</math>)</b>	3
<b>Sensitivity (dB SPL) <sup>1</sup></b>	95
<b>Frequency Range (Hz)</b>	900 - 7,000
<b>Resonant Frequency (Fs) (Hz)</b>	1150

### More Specifications

<b>Application</b>	Aerospace, Signal / Alarm Systems
<b>DC Resistance (Re) (<math>\Omega</math>)</b>	2.7
<b>Program Power (W)</b>	5

### Small Signal Parameters

<b>Nominal Impedance (Z) (<math>\Omega</math>)</b>	3
<b>DC Resistance (Re) (<math>\Omega</math>)</b>	2.7
<b>Voice Coil Inductance (Le) (mH)</b>	2.7
<b>Resonant Frequency (Fs) (Hz)</b>	1150

### Material Descriptions

<b>Basket Type</b>	Steel
<b>Terminal Size (mm)</b>	2.8 x 0.5
<b>Voice Coil Diameter (mm)</b>	14.5
<b>Voice Coil Wire Material</b>	Copper
<b>Voice Coil Former Material</b>	Aluminum
<b>Magnet Material</b>	Alnico
<b>Magnet Weight (g)</b>	15
<b>Cone Body Material</b>	Acrylic treated cloth
<b>Cone Surround Material</b>	Acrylic treated cloth
<b>Dust Cap Material</b>	Acrylic treated cloth
<b>Net Weight (kg)</b>	0.05

